



GXP2110 is the next generation enterprise grade IP phone that 4 lines, a large 240X 120 backlit graphical LCD, 3 XML programmable context-sensitive soft keys, 18 XML programmable BLF extension keys, dual network ports with integrated PoE, and 5-way conference. The GXP2110 delivers superiors HD audio quality, rich and leading edge telephony features, personalized information and customizable application service, automated provisioning for easy deployment, advanced security protection for privacy, and broad interoperability with 3rd party SIP devices and leading SIP/NGN/IMS platforms. It is perfect choice for enterprise users looking for a high quality, feature rich multi-line IP phone with numerous extension keys.

Feature Highlights

- Large 240 X 120 pixel backlit graphical LCD display with up to 8 level grayscale
- 4 dual-color line keys (with 4 SIP accounts), 3 XML programmable context-sensitive soft keys, up to 5-way conference, and up to 22 call appearances with 18 dual-color BLF extension keys
- HD wideband audio, superb full-duplex hands-free speakerphone with advanced acoustic echo cancellation and excellent double-talk performance
- Large phonebook (up to 2,000 contacts) and call history (up to 2,000 records)
- Automated personal information service (e.g., local weather, stock, currencies, RSS news etc), personalized music ring tone/ring back tone/music-on-hold, flexible customizable screen content & format using XML, and advanced Web and enterprise applications integration (pending)
- Dual switched auto-sensing 10/100Mbps network ports with integrated PoE
- Automated provisioning using TR-069 or encrypted XML configuration file SRTP and TLS for advanced security protection, 802.1x for media access control

Protocols/ Standards	:	SIP RFC 3261, TCP/IP/UDP, RTP/RTCP, HTTP/HTT[S, ARP/RARP, ICMA DNS (A record, SRV, NAPTR) DHCP, PPPoE, TE; MET, TFTP, NTP, STUN, SIMPLE, TR-069, 802.1X, IPV6 (pending)
Network interfaces	:	Dual switched 10/100Mbps ports with integrated Poe
Graphic Display	:	Back-lit 240x 120 graphical LCD display with up to 8 level grayscale
Feature Keys	:	4 line key with dual-color LED and 4 independent SIP accounts, 18 Programmable BLF extension keys with dual – color LED, 3 XML Programmable context sensitive soft keys, 5 navigation/men/volume Keys, 11 dedicated function keys for: HOLD SPEAKERPHONE, SEND/REDIAL, TRANSFER, CONFERENCE, MUTE, HEADSET, INTERCOM/PAGING, DO-NOT-DISTURB, PHONEBOOK, and MESSAGE (With LED indicator)
Voice Coded	:	Hold, transfer, forward, 5-way conference, busy-lamp-field (BLF), Call Park, pickup, shared-call-appearance (SCA)/bridged-line-appearance (BLA), downloadable phone book (XML, LDAP, up to 2,000 items), call waiting, call log (up to 2,000 records), XML customization of screen, Off-hook auto dial answer, click-to-dial, flexible dial plan, hot desking, Personalized music ringtones and music on hold, server redundancy and fail-over.
HD Audio	:	Yes, both on handset and speakerphone
Headset Jack	:	Both RJ9 and 2.5mm jacks for professional and casual use
Base Stand	:	Yes, allows 2 angle positions
Wall Mountable	:	Yes
Expansion Module	:	Allow up to 2 externally attached expansion modules and 112 extra keys
QoS	:	Layer 2 (802.2p) and Layer 3 (ToS, Diffserv, MPLS) QoS)
Security	:	User and administer level passwords, MD5 and MD5-sess based authentication, AES based secure configuration files, SRTP, TLS, 802.1x media access control
Multi-language	:	Yes (English, German, Italian, French, Spanish, Chinese, Korean, Japanese, etc)
Upgrade/Provisioning	:	Firmware upgrade via TFTP/HTTP/HTTPS, mass provisioning using TR-069 or encrypted XML configuration files
Power & Green energy Efficiency	:	Universal power adapter included: input; 100240VAC 50-60Hz; Output: 5 VDC, 800mA); Integrated Power-over-Ethernet (802.3af); Max power Consumption 2.5W (poweradapter) or 3W (PoE)
Temperature and Humidity	:	32-104°F/0-40°C, 10-90% (non condensing)
Package content	:	GXP2110 phone, handset with cord, base stand, universal power supply, network cable, Quick start Guide
Compliance	:	FCC Part 15 (CFR 47) Class B; EN55022 Class B, EN55024, EN61000-3-2, EN61000-3-3 EN60950-1; AS/NZS CISPR 22 Class B, AS/NZS CISPR 24, RoHS; UL 60950 (power adapter)